

AMESIA

INDOOR P3.9 / P4.8 - OUTDOOR P6.25 / P7.8



TAGLIG
AMESIA



General Properties

- Sturdy Ergonomic Structure
- Easy and Powerful Lock System
- High-Power Passive Cooling System
- Light and Easily Portable Cabin with a 500x500 Measurement
- Technical Intervention from Behind
- Rental, Fixed, Indoor, and Outdoor



ULTRA BRIGHT



HIGH VIEWING ANGLE



OUTDOOR



HIGH REFRESH RATE



FANLESS DESIGN



HD HIGH DEFINITION



IP 65



EASY MAINTENANCE



MOBILE SYSTEM COMPATIBLE



NO GHOST (CLEAN IMAGE)



ENERGY SAVING



24/7 USAGE



EASY INSTALLATION



INDOOR



IP 54



9.7 KG

Technical Properties	INDOOR		OUTDOOR	
Pixel	P3.9	P4.8	P6.25	P7.8
Led Type	SMD2020	SMD2020	SMD3535	SMD3535
Brightness	1200nits/m2	1250nits/m2	7500nits/m2	7500nits/m2
Refresh Rate	1920Hz	1920Hz	1920Hz	1920Hz
Driving Method	1/16	1/13	1/8	1/3
Module Size	250x250	250x250	250x250	250x250
Module Resolution	64x64	52x52	40x40	32x32
Cabinet Size	500x500	500x500	500x500	500x500
Pixel Density	65536	43264	25600	16384
Max. Power	480	440	780	700
Avg. Power	300	270	440	400
IC Driver	MBI5124	MBI5124	MBI5124	MBI5124
Power Supply	MEANWELL 5V60A	MEANWELL 5V60A	MEANWELL 5V60A	MEANWELL 5V60A
Module Per Cabinet	4	4	4	4
Weight Cabinet	9,7 Kg	9,7 Kg	9,7 Kg	9,7 Kg
Colors	281 Trillion	281 Trillion	281 Trillion	281 Trillion
Min. Viewing Distance	3 mt	4 mt	6 mt	7 mt
Horizontal Viewing Angle	140	140	140	140
Vertical Viewing Angle	140	140	140	140
Led Lifetime	100.000 hours	100.000 hours	100.000 hours	100.000 hours
Input Voltage	110-240V	110-240V	110-240V	110-240V
Operation Temperature	--40+ 70 C	--40+ 70 C	--40+ 70 C	--40+ 70 C
Ingress Protection	IP54	IP54	IP65	IP65
Gray Level	65536	65536	65536	65536

